

Aprisa XE

POINT-TO-POINT DIGITAL MICROWAVE LINKS NTIA 2000 MHz licensed band



2000 MHz Aprisa XE: maximizing spectrum use and making challenging long distance links possible


- **Efficient future-proof single-box architecture:** the Aprisa XE's built-in multiplexer and cross-connect eliminate external equipment and minimize the over-the-air requirements, with customer-configurable interface slots integrating all IP, voice and data traffic. Configuration, performance monitoring and diagnostics are easy with the 4RF embedded web-based element management system, SuperVisor.
- **High capacity:** class-leading spectral efficiency and up to 128 QAM modulation make the maximum use of the available spectrum, with industry leading capacity of up to 2792 kbit/s in a 500 kHz channel.
- **Long range:** a single 2000 MHz Aprisa XE can link distances in excess of 80 miles, overcoming the problems of water, environmental conditions and topographical obstacles.
- **Carrier-class performance:** Aprisa XE links are engineered to achieve 'five 9s' availability, benefiting from state of the art forward error correction and inherent low latencies, for unrivaled quality of service.
- **Cost effective:** the Aprisa XE has a low total cost of ownership, providing a rapid return on investment by minimizing both capital and operational expenditure.
- **Reliable:** the Aprisa XE has an actual MTBF of 95.72 years, and zero out-of-the-box failures in 2008. It can be relied upon to perform in the harshest and most remote environments.



The Aprisa XE in brief

- Licensed 2000 MHz frequency band
- Built-in cross-connect and multiplexer
- Up to 2792 kbit/s capacity
- 500 kHz channel size
- QPSK to 128 QAM modulation
- Range of 80+ miles
- Industry-leading reliability
- Web server and SNMP management
- All voice, data and IP applications

Future-proof single-box architecture



SYSTEM SPECIFICATION

RF	BAND	TUNING RANGE	SYNTHESIZER STEP SIZE
FREQUENCIES	2000 MHz	1900 – 2300 MHz	62.5 kHz
MODULATION TYPES	Software configurable: QPSK / 16 / 32 / 64 / 128 QAM		
FREQUENCY STABILITY	Short term ± 1 ppm (environmental effects and power supply variations) Long term ± 2 ppm (aging of crystal oscillators ≈ over 5 years)		
ANTENNA CONNECTION	N-type female 50 ohm		
TRANSMITTER			
QPSK	+20 dBm to +34 dBm		
16 QAM	+17 dBm to +31 dBm		
32 QAM	+16 dBm to +30 dBm		
64 QAM	+15 dBm to +29 dBm		
128 QAM	+15 dBm to +29 dBm		
RECEIVER			
MAXIMUM INPUT LEVEL	-20 dBm		
DYNAMIC RANGE	58 to 87 dB at 10 ⁻⁶ BER		
C/I RATIO	Co-channel	QPSK	better than 16 dB
		16 QAM	better than 20 dB
		32 QAM	better than 23 dB
		64 QAM	better than 27 dB
		128 QAM	better than 30 dB
		First adjacent channel	better than -5 dB
	Second adjacent channel	better than -30 dB	
DUPLEXER (bandpass)	PASSBAND	TX / RX SPLIT	TUNING RANGE
10	14 MHz	≥ 91 MHz	1900 – 2300 MHz
POWER SUPPLY			
INPUT RANGE	115 / 230 VAC, 50 / 60 Hz ±24 VDC (20.5 – 30 VDC), ±48 VDC (40 – 60 VDC)		
POWER CONSUMPTION	53 – 180 W input power (dependent on interface cards fitted and transmitter output power level)		

INTERFACES	
ETHERNET	Integrated 4-port 10/100Base-T switch with port-based rate limiting, VLAN tagging and QoS Support
E1 / T1	Quad 120 ohm G.703 / 4
DATA	Quad V.24 asynchronous, synchronous and over sampling mode Single synchronous X.21 / V.35 / RS-449 / RS-530
ANALOG	Dual 2-wire FXS / FXO (POTS); Quad 4-wire E&M
AUXILIARY INTERFACES	
ALARMS	4 external alarm outputs, 2 external alarm inputs
CONFIGURATION	Embedded web server with SNMP
MANAGEMENT	Ethernet interface for SuperVisor and SNMP; V.24 setup port
RSSI	Front panel test point
ENVIRONMENTAL	
OPERATING	+14° F to +122° F (-10° C to +50° C)
STORAGE	-4° F to +158° F (-20° C to +70° C)
HUMIDITY	Maximum 95 % non-condensing
MECHANICAL	
RACK MOUNT	19" 2U high (internal duplexer)
WEIGHT	23 lbs (10 kg) typical
COMPLIANCE	
RADIO	NTIA
EMI / EMC	FCC CFR 47 Part 15, EN 301 489 Parts 1 & 4
SAFETY	EN 60950 CSA 253147 applicable for AC, 48 VDC and 24 VDC product variants
ENVIRONMENTAL	ETS 300 019 Class 3.2, WEEE

SYSTEM PERFORMANCE

500 kHz CHANNEL		QPSK	16 QAM	32 QAM	64 QAM	128 QAM ³
CAPACITY ¹	gross (T1 + wayside)	792 (12 TS + 24) kbit/s	1592 (1 T1 + 8) kbit/s	1992 (1 T1 + 408) kbit/s	2392 (1 T1 + 808) kbit/s	2792 (1 T1 + 1208) kbit/s
RECEIVER SENSITIVITY ²		-99 dBm	-93 dBm	-90 dBm	-87 dBm	-84 dBm
SYSTEM GAIN ²		133 dB	124 dB	120 dB	116 dB	113 dB

NOTES

- T1 capacities are specified as unframed. The management Ethernet capacity must be subtracted from the gross capacity (default 64 kbit/s).
- Performance specified at the antenna port for 10⁻⁶ BER. Figures for 10⁻³ BER are typically 1 dB better.
- Unreleased: Please contact 4RF for availability.

ABOUT 4RF

Operating in more than 130 countries, 4RF provides radio communications equipment for critical infrastructure applications. Customers include utilities, oil and gas companies, transport companies, telecommunications operators, international aid organisations, public safety, military and security organisations. 4RF point-to-point and point-to-multipoint products are optimized for performance in harsh climates and difficult terrain, supporting IP, legacy analog, serial data and PDH applications.

Copyright © 2012 4RF Limited. All rights reserved. This document is protected by copyright belonging to 4RF Limited and may not be reproduced or republished in whole or part in any form without the prior written consent of 4RF Limited. While every precaution has been taken in the preparation of this literature, 4RF Limited assumes no liability for errors or omissions, or from any damages resulting from the use of this information. The contents and product specifications within it are subject to revision due to ongoing product improvements and may change without notice. Aprisa and the 4RF logo are trademarks of 4RF Limited. Version 9.2.1



For more information please contact
EMAIL sales@4rf.com
URL www.4rf.com